

NEW SOLUTION

Solar 4WD Professional Autonomous VITIROVER ROBOT MOWER



Get rid of Glyphosate, Plowing and Massive Tractors!

VITIROVER Professional Robot Mower

A very effective and ecological solution to maintain vegetation without damaging soils nor trees.

Vitirover mows unwanted vegetation within designated plots. It goes very gently, in contact with obstacles such as trees, stakes or pilars, to cut unwanted vegetation as close to them as possible.





Green and autonomous

VITIROVER produces its own solar energy. It is autonomous and does not consume any fossil fuels.

No more chemical weeding

VITIROVER preserves the environment by providing precise weed control without the use of chemical weedkillers or tillage.

Respect the soil

VITIROVER respects the soil thanks to its light weight, avoiding compaction caused by large tractors.

Zero damage

VITIROVER cannot damage or destroy plants or industrial installation supports. It smoothly get close to obstacles (trees, vines or pilars) at a very low speed.

OUR MARKETS



Coming from
Vineyards, one of the
toughest agricultural
environment to
maintain because of
the density of
obstacles, VITIROVER
robots have adapted
to many other
environment.





ECO-FRIENDLY



ESG LEADER



COST SAVING



SOLAR ENERGY



AUTONOMOUS

CHARGING DOCK STATION




The solar panel mounted on top of VITIROVER allows the robot to work up to 6 hours a day, depending on the sunshine.

For the robot to work daily and permanently, the VITIROVER Charging Dock Station can be installed on any agricultural or industrial plot.

WEB REMOTE DASHBOARD

The Viti-Cloud web-based dashboard allows the robots' shepherds (robots fleet managers) to monitor, maintain, manage and even remotely drive robots. The dashboard will provide live technical information such as battery level, motor consumption, mowing efficiency, plot coverage, etc. It will also publish detailed data reports. The robots shepherd will be able to take over robots thanks to a remote and live transmission from the cameras.



INTERNATIONAL RECOGNITION





























SPECIFICATIONS	VR OUTDOOR	VR UNIVERSITY
DIMENSIONS [cm] (LxWxH)	75 cm x 40 cm x 30 cm	75 cm x 40 cm x 30 cm
DIMENSIONS [in] (L x W x H)	29"1/2 x 15"3/4 x 11"3/4	29"1/2 x 15"3/4 x 11"3/4
WEIGHT (kg / lbs)	27 kg - 59 lbs	24 kg - 53 lbs
CONSUMPTION	1 W/kg - 0.45 W/lb	1 W/kg - 0.45 W/lb
AUTONOMOUS MOVEMENT	YES	YES
MAX SPEED	900 m/h - 55 MPH	900 m/h - 55 MPH
WHEEL DRIVE	4 WD	4 WD
DRIVE MOTORS	4 (1 per axle)	4 (1 per axle)
SOUND LEVEL (dBA)	40 dBA	40 dBA
MAX SLOPE (based upon soil)	15 to 20%	15 to 20%
WEB BASED DASHBOARD	YES	YES
CUTTING BLOCK	2 Rotating Grinders	OPTION
OUTTING HEIGHT (cm / in)	5 to 10 cm - 2" to 4"	
OUTTING WIDTH (cm / in)	30 cm - 11"3/4	
PRECISION TO OBSTACLE	< 1cm - < 1/2"	
FRONT CAMERAS (RGB)	2	2
INERTIAL SENSOR	IMU	IMU
POWER SUPPLY	Solar Panel	Solar Panel
CHARGING DOCK STATION	Solar / Direct	OPTION
GEOLOCATION (GNSS)	GPS, GLONASS BEIDOU, GALILEO	GPS, GLONASS BEIDOU, GALILEO
GEOLOCATION (RTK)	YES (License included)	YES (License not included)
SECURITY GEOLOCATION	Security Battery	Security Battery
ANTI-THEFT / SAFETY SHUT-OFF	Remote / Lift / Auto	Remote / Lift / Auto
SAFETY FEATURE	Lift Auto Shut Off	Lift Auto Shut Off
EMISSIONS (CO2/Chemicals)	0	0
SOFT DESIGN KIT		Protobuf (JSON) via USB
ROBOT OPERATING SYSTEM		ROS2 Compatible
OPTIONAL SENSORS		LIDAR / Ultrasound



Research & Development

6 Lieu-dit SIMARD, La Gare, 33330 Saint Emilion, FRANCE

Sales Office

23 place Jean Moulin, 33500 Libourne, FRANCE

CONTACT



info@vitirover.com



Sébastien : (+33) 6 79 24 35 08 Arnaud : (+33) 6 07 61 23 36



vitirover.com







@Vitirover